





Niethülse **Aluminium**
 Nietdorn **Stahl verzinkt**
 Flachrundkopf





DIN EN ISO 15977

$\varnothing d$	l	min - max	\varnothing	$\varnothing d_k$	k max.	$\varnothing d_m$ max.	p min.	[N]	[N]	Code
2.4	4.0	0.5 - 2.0	2.5 - 2.6	5.0	1.0	1.55	25	350	250	10ASI2404
	6.0	2.0 - 4.0	2.5 - 2.6	5.0	1.0	1.55	25	350	250	10ASI2406
	8.0	4.0 - 6.0	2.5 - 2.6	5.0	1.0	1.55	25	350	250	10ASI2408
	10.0	6.0 - 8.0	2.5 - 2.6	5.0	1.0	1.55	25	350	250	10ASI2410
	12.0	8.0 - 9.5	2.5 - 2.6	5.0	1.0	1.55	25	350	250	10ASI2412
3.0	4.0	0.5 - 1.5	3.1 - 3.2	6.0	1.3	2.00	25	550	400	10ASI3004
	6.0	1.5 - 3.5	3.1 - 3.2	6.0	1.3	2.00	25	550	400	10ASI3006
	8.0	3.5 - 5.0	3.1 - 3.2	6.0	1.3	2.00	25	550	400	10ASI3008
	10.0	5.0 - 7.0	3.1 - 3.2	6.0	1.3	2.00	25	550	400	10ASI3010
	12.0	7.0 - 9.0	3.1 - 3.2	6.0	1.3	2.00	25	550	400	10ASI3012
	14.0	9.0 - 11.0	3.1 - 3.2	6.0	1.3	2.00	25	550	400	10ASI3014
	16.0	11.0 - 13.0	3.1 - 3.2	6.0	1.3	2.00	25	550	400	10ASI3016
	18.0	13.0 - 15.0	3.1 - 3.2	6.0	1.3	2.00	25	550	400	10ASI3018
	20.0	15.0 - 17.0	3.1 - 3.2	6.0	1.3	2.00	25	550	400	10ASI3020
3.2	4.0	0.5 - 1.5	3.3 - 3.4	6.0	1.3	2.00	25	700	500	10ASI3204
	6.0	1.5 - 3.5	3.3 - 3.4	6.0	1.3	2.00	25	700	500	10ASI3206
	8.0	3.5 - 5.0	3.3 - 3.4	6.0	1.3	2.00	25	700	500	10ASI3208
	10.0	5.0 - 7.0	3.3 - 3.4	6.0	1.3	2.00	25	700	500	10ASI3210
	12.0	7.0 - 9.0	3.3 - 3.4	6.0	1.3	2.00	25	700	500	10ASI3212
	14.0	9.0 - 11.0	3.3 - 3.4	6.0	1.3	2.00	25	700	500	10ASI3214
	16.0	11.0 - 13.0	3.3 - 3.4	6.0	1.3	2.00	25	700	500	10ASI3216
	18.0	13.0 - 15.0	3.3 - 3.4	6.0	1.3	2.00	25	700	500	10ASI3218
	20.0	15.0 - 17.0	3.3 - 3.4	6.0	1.3	2.00	25	700	500	10ASI3220
	25.0	17.0 - 22.0	3.3 - 3.4	6.0	1.3	2.00	25	700	500	10ASI3225
4.0	6.0	1.0 - 3.0	4.1 - 4.2	8.0	1.7	2.45	27	1700	1100	10ASI4006
	8.0	3.0 - 5.0	4.1 - 4.2	8.0	1.7	2.45	27	1700	1100	10ASI4008
	10.0	5.0 - 6.5	4.1 - 4.2	8.0	1.7	2.45	27	1700	1100	10ASI4010
	12.0	6.5 - 8.5	4.1 - 4.2	8.0	1.7	2.45	27	1700	1100	10ASI4012
	14.0	8.5 - 10.5	4.1 - 4.2	8.0	1.7	2.45	27	1700	1100	10ASI4014
	16.0	10.5 - 12.5	4.1 - 4.2	8.0	1.7	2.45	27	1700	1100	10ASI4016
	18.0	12.5 - 14.5	4.1 - 4.2	8.0	1.7	2.45	27	1700	1100	10ASI4018





Q-Standard



Niethülse **Aluminium**
 Nietdorn **Stahl verzinkt**
 Flachrundkopf





DIN EN ISO 15977

$\varnothing d$	l	 min - max	 \varnothing	$\varnothing d_k$	k max.	$\varnothing d_m$ max.	p min.	 [N]	 [N]	Code
mm	mm	mm	mm	mm	mm	mm	mm	[N]	[N]	
4.0	20.0	14.5 - 16.5	4.1 - 4.2	8.0	1.7	2.45	27	1700	1100	10AS14020
	23.0	16.0 - 19.0	4.1 - 4.2	8.0	1.7	2.45	27	1700	1100	10AS14023
	25.0	16.5 - 21.0	4.1 - 4.2	8.0	1.7	2.45	27	1700	1100	10AS14025
	30.0	21.0 - 25.0	4.1 - 4.2	8.0	1.7	2.45	27	1700	1100	10AS14030
	35.0	25.0 - 30.0	4.1 - 4.2	8.0	1.7	2.45	27	1700	1100	10AS14035
4.8	6.0	1.5 - 2.5	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	10AS14806
	8.0	2.5 - 4.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	10AS14808
	10.0	4.0 - 6.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	10AS14810
	12.0	6.0 - 8.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	10AS14812
	14.0	7.0 - 9.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	10AS14814
	16.0	8.0 - 12.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	10AS14816
	18.0	11.0 - 13.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	10AS14818
	20.0	12.0 - 15.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	10AS14820
	22.0	14.0 - 17.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	10AS14822
	25.0	15.0 - 20.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	10AS14825
	28.0	18.0 - 23.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	10AS14828
	30.0	20.0 - 25.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	10AS14830
	35.0	25.0 - 30.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	10AS14835
	40.0	30.0 - 35.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	10AS14840
	45.0	35.0 - 40.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	10AS14845
	50.0	40.0 - 45.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	10AS14850
	55.0	45.0 - 50.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	10AS14855
	60.0	50.0 - 55.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	10AS14860
5.0	6.0	1.5 - 2.5	5.1 - 5.2	9.5	2.1	2.95	27	2950	1950	10AS15006
	8.0	2.5 - 4.0	5.1 - 5.2	9.5	2.1	2.95	27	2950	1950	10AS15008
	10.0	4.0 - 6.0	5.1 - 5.2	9.5	2.1	2.95	27	2950	1950	10AS15010
	12.0	6.0 - 8.0	5.1 - 5.2	9.5	2.1	2.95	27	2950	1950	10AS15012
	14.0	7.0 - 9.0	5.1 - 5.2	9.5	2.1	2.95	27	2950	1950	10AS15014
	16.0	8.0 - 12.0	5.1 - 5.2	9.5	2.1	2.95	27	2950	1950	10AS15016
	18.0	11.0 - 13.0	5.1 - 5.2	9.5	2.1	2.95	27	2950	1950	10AS15018
	20.0	14.0 - 16.0	5.1 - 5.2	9.5	2.1	2.95	27	2950	1950	10AS15021
	25.0	15.0 - 20.0	5.1 - 5.2	9.5	2.1	2.95	27	2950	1950	10AS15025



Niethülse **Aluminium**
 Nietdorn **Stahl verzinkt**
 Flachrundkopf



DIN EN ISO 15977

$\varnothing d$	l	min - max	\varnothing	$\varnothing d_k$	k max.	$\varnothing d_m$ max.	p min.	[N]	[N]	Code
mm	mm	mm	mm	mm	mm	mm	mm	[N]	[N]	
5.0	27.0	20.0 - 22.0	5.1 - 5.2	9.5	2.1	2.95	27	2950	1950	10AS15027
	30.0	22.0 - 25.0	5.1 - 5.2	9.5	2.1	2.95	27	2950	1950	10AS15030
	35.0	25.0 - 30.0	5.1 - 5.2	9.5	2.1	2.95	27	2950	1950	10AS15035
	40.0	30.0 - 35.0	5.1 - 5.2	9.5	2.1	2.95	27	2950	1950	10AS15040
	45.0	35.0 - 40.0	5.1 - 5.2	9.5	2.1	2.95	27	2950	1950	10AS15045
	50.0	40.0 - 45.0	5.1 - 5.2	9.5	2.1	2.95	27	2950	1950	10AS15050
6.0	8.0	2.0 - 3.0	6.1 - 6.2	12.0	2.5	3.40	27	4200	3200	10AS16008
	10.0	3.0 - 5.0	6.1 - 6.2	12.0	2.5	3.40	27	4200	3200	10AS16010
	12.0	5.0 - 7.0	6.1 - 6.2	12.0	2.5	3.40	27	4200	3200	10AS16012
	14.0	6.0 - 8.0	6.1 - 6.2	12.0	2.5	3.40	27	4200	3200	10AS16014
	16.0	7.0 - 11.0	6.1 - 6.2	12.0	2.5	3.40	27	4200	3200	10AS16016
	18.0	10.0 - 12.0	6.1 - 6.2	12.0	2.5	3.40	27	4200	3200	10AS16018
	22.0	12.0 - 16.0	6.1 - 6.2	12.0	2.5	3.40	27	4200	3200	10AS16022
	26.0	15.0 - 20.0	6.1 - 6.2	12.0	2.5	3.40	27	4200	3200	10AS16026
30.0	20.0 - 25.0	6.1 - 6.2	12.0	2.5	3.40	27	4200	3200	10AS16030	
6.4	10.0	1.0 - 3.0	6.5 - 6.6	13.0	2.7	3.90	27	4850	3400	10AS16410
	12.0	3.0 - 6.0	6.5 - 6.6	13.0	2.7	3.90	27	4850	3400	10AS16412
	15.0	6.0 - 9.0	6.5 - 6.6	13.0	2.7	3.90	27	4850	3400	10AS16415
	18.0	9.0 - 12.0	6.5 - 6.6	13.0	2.7	3.90	27	4850	3400	10AS16418
	22.0	12.0 - 15.0	6.5 - 6.6	13.0	2.7	3.90	27	4850	3400	10AS16422
	26.0	15.0 - 19.0	6.5 - 6.6	13.0	2.7	3.90	27	4850	3400	10AS16426
	30.0	18.0 - 23.0	6.5 - 6.6	13.0	2.7	3.90	27	4850	3400	10AS16430
	35.0	23.0 - 28.0	6.5 - 6.6	13.0	2.7	3.90	27	4850	3400	10AS16435
40.0	28.0 - 33.0	6.5 - 6.6	13.0	2.7	3.90	27	4850	3400	10AS16440	