





Niethülse **Stahl verzinkt**  
 Nietdorn **Stahl verzinkt**  
 Flachrundkopf





DIN EN ISO 15979

$\varnothing d$	$l$	min - max	Ø	$\varnothing d_k$	$k$ max.	$\varnothing d_m$ max.	$p$ min.	[N]	[N]	Code
	mm	mm	mm	mm	mm	mm	mm	[N]	[N]	
<b>3.0</b>	<b>5.0</b>	0.5 - 2.0	3.1 - 3.2	6.0	1.3	2.15	25	1100	950	<b>10SS13005</b>
	<b>6.0</b>	0.5 - 3.0	3.1 - 3.2	6.0	1.3	2.15	25	1100	950	<b>10SS13006</b>
	<b>8.0</b>	3.0 - 5.0	3.1 - 3.2	6.0	1.3	2.15	25	1100	950	<b>10SS13008</b>
	<b>10.0</b>	5.0 - 6.5	3.1 - 3.2	6.0	1.3	2.15	25	1100	950	<b>10SS13010</b>
	<b>12.0</b>	6.5 - 8.0	3.1 - 3.2	6.0	1.3	2.15	25	1100	950	<b>10SS13012</b>
	<b>14.0</b>	8.0 - 10.0	3.1 - 3.2	6.0	1.3	2.15	25	1100	950	<b>10SS13014</b>
	<b>16.0</b>	10.0 - 12.0	3.1 - 3.2	6.0	1.3	2.15	25	1100	950	<b>10SS13016</b>
	<b>18.0</b>	12.0 - 14.0	3.1 - 3.2	6.0	1.3	2.15	25	1100	950	<b>10SS13018</b>
	<b>20.0</b>	14.0 - 16.0	3.1 - 3.2	6.0	1.3	2.15	25	1100	950	<b>10SS13020</b>
<b>3.2</b>	<b>5.0</b>	0.5 - 2.0	3.3 - 3.4	6.0	1.3	2.15	25	1200	1100	<b>10SS13205</b>
	<b>6.0</b>	0.5 - 3.0	3.3 - 3.4	6.0	1.3	2.15	25	1200	1100	<b>10SS13206</b>
	<b>8.0</b>	3.0 - 5.0	3.3 - 3.4	6.0	1.3	2.15	25	1200	1100	<b>10SS13208</b>
	<b>10.0</b>	5.0 - 6.5	3.3 - 3.4	6.0	1.3	2.15	25	1200	1100	<b>10SS13210</b>
	<b>12.0</b>	6.5 - 8.0	3.3 - 3.4	6.0	1.3	2.15	25	1200	1100	<b>10SS13212</b>
	<b>14.0</b>	8.0 - 10.0	3.3 - 3.4	6.0	1.3	2.15	25	1200	1100	<b>10SS13214</b>
	<b>16.0</b>	10.0 - 12.0	3.3 - 3.4	6.0	1.3	2.15	25	1200	1100	<b>10SS13216</b>
	<b>18.0</b>	12.0 - 14.0	3.3 - 3.4	6.0	1.3	2.15	25	1200	1100	<b>10SS13218</b>
	<b>20.0</b>	14.0 - 16.0	3.3 - 3.4	6.0	1.3	2.15	25	1200	1100	<b>10SS13220</b>
<b>4.0</b>	<b>6.0</b>	1.0 - 3.0	4.1 - 4.2	8.0	1.7	2.80	27	2000	1700	<b>10SS14006</b>
	<b>8.0</b>	3.0 - 5.0	4.1 - 4.2	8.0	1.7	2.80	27	2000	1700	<b>10SS14008</b>
	<b>10.0</b>	5.0 - 6.5	4.1 - 4.2	8.0	1.7	2.80	27	2000	1700	<b>10SS14010</b>
	<b>12.0</b>	6.5 - 9.0	4.1 - 4.2	8.0	1.7	2.80	27	2000	1700	<b>10SS14012</b>
	<b>14.0</b>	7.5 - 10.0	4.1 - 4.2	8.0	1.7	2.80	27	2000	1700	<b>10SS14014</b>
	<b>16.0</b>	9.0 - 12.0	4.1 - 4.2	8.0	1.7	2.80	27	2000	1700	<b>10SS14016</b>
	<b>18.0</b>	11.0 - 14.0	4.1 - 4.2	8.0	1.7	2.80	27	2000	1700	<b>10SS14018</b>
	<b>20.0</b>	12.0 - 16.0	4.1 - 4.2	8.0	1.7	2.80	27	2000	1700	<b>10SS14020</b>
	<b>22.0</b>	15.0 - 17.0	4.1 - 4.2	8.0	1.7	2.80	27	2000	1700	<b>10SS14022</b>
	<b>24.0</b>	16.0 - 19.0	4.1 - 4.2	8.0	1.7	2.80	27	2000	1700	<b>10SS14024</b>
	<b>25.0</b>	17.0 - 20.0	4.1 - 4.2	8.0	1.7	2.80	27	2000	1700	<b>10SS14025</b>
	<b>26.0</b>	18.0 - 21.0	4.1 - 4.2	8.0	1.7	2.80	27	2000	1700	<b>10SS14026</b>
	<b>30.0</b>	21.0 - 25.0	4.1 - 4.2	8.0	1.7	2.80	27	2000	1700	<b>10SS14030</b>





## Q-Standard



Niethülse **Stahl verzinkt**  
 Nietdorn **Stahl verzinkt**  
 Flachrundkopf





DIN EN ISO 15979

$\varnothing d$	$l$	 min - max	 $\varnothing$	$\varnothing d_k$	$k$ max.	$\varnothing d_m$ max.	$p$ min.	 [N]	 [N]	Code
mm	mm	mm	mm	mm	mm	mm	mm	[N]	[N]	
4.8	6.0	1.0 - 2.0	4.9 - 5.0	9.5	2.0	3.50	27	3100	2900	10SS14806
	8.0	2.5 - 4.0	4.9 - 5.0	9.5	2.0	3.50	27	3100	2900	10SS14808
	10.0	4.0 - 6.0	4.9 - 5.0	9.5	2.0	3.50	27	3100	2900	10SS14810
	12.0	6.0 - 8.0	4.9 - 5.0	9.5	2.0	3.50	27	3100	2900	10SS14812
	14.0	7.0 - 9.0	4.9 - 5.0	9.5	2.0	3.50	27	3100	2900	10SS14814
	16.0	8.0 - 11.0	4.9 - 5.0	9.5	2.0	3.50	27	3100	2900	10SS14816
	18.0	10.0 - 13.0	4.9 - 5.0	9.5	2.0	3.50	27	3100	2900	10SS14818
	20.0	11.0 - 15.0	4.9 - 5.0	9.5	2.0	3.50	27	3100	2900	10SS14820
	22.0	13.0 - 17.0	4.9 - 5.0	9.5	2.0	3.50	27	3100	2900	10SS14822
	25.0	15.0 - 19.5	4.9 - 5.0	9.5	2.0	3.50	27	3100	2900	10SS14825
28.0	19.0 - 23.0	4.9 - 5.0	9.5	2.0	3.50	27	3100	2900	10SS14828	
30.0	19.5 - 25.0	4.9 - 5.0	9.5	2.0	3.50	27	3100	2900	10SS14830	
5.0	8.0	2.5 - 4.0	5.1 - 5.2	9.5	2.1	3.50	27	4000	3100	10SS15008
	10.0	4.0 - 6.0	5.1 - 5.2	9.5	2.1	3.50	27	4000	3100	10SS15010
	12.0	6.0 - 8.0	5.1 - 5.2	9.5	2.1	3.50	27	4000	3100	10SS15012
	14.0	7.0 - 9.0	5.1 - 5.2	9.5	2.1	3.50	27	4000	3100	10SS15014
	16.0	8.0 - 11.0	5.1 - 5.2	9.5	2.1	3.50	27	4000	3100	10SS15016
	18.0	10.0 - 13.0	5.1 - 5.2	9.5	2.1	3.50	27	4000	3100	10SS15018
	20.0	11.0 - 15.0	5.1 - 5.2	9.5	2.1	3.50	27	4000	3100	10SS15020
	22.0	13.0 - 17.0	5.1 - 5.2	9.5	2.1	3.50	27	4000	3100	10SS15022
	25.0	15.0 - 19.5	5.1 - 5.2	9.5	2.1	3.50	27	4000	3100	10SS15025
	30.0	19.5 - 25.0	5.1 - 5.2	9.5	2.1	3.50	27	4000	3100	10SS15030



Niethülse **Stahl verzinkt**  
 Nietdorn **Stahl verzinkt**  
 Flachrundkopf



DIN EN ISO 15979

$\varnothing d$	$l$	min - max	$\varnothing$	$\varnothing d_k$	$k$ max.	$\varnothing d_m$ max.	$p$ min.	[N]	[N]	Code
mm	mm	mm	mm	mm	mm	mm	mm	[N]	[N]	
6.0	10.0	3.0 - 4.0	6.1 - 6.2	12.0	2.5	4.00	27	4800	4300	10SS16010
	12.0	4.0 - 6.0	6.1 - 6.2	12.0	2.5	4.00	27	4800	4300	10SS16012
	14.0	6.0 - 8.0	6.1 - 6.2	12.0	2.5	4.00	27	4800	4300	10SS16014
	15.0	7.0 - 9.0	6.1 - 6.2	12.0	2.5	4.00	27	4800	4300	10SS16015
	16.0	6.0 - 10.0	6.1 - 6.2	12.0	2.5	4.00	27	4800	4300	10SS16016
	18.0	10.0 - 12.0	6.1 - 6.2	12.0	2.5	4.00	27	4800	4300	10SS16018
	22.0	12.0 - 16.0	6.1 - 6.2	12.0	2.5	4.00	27	4800	4300	10SS16022
	26.0	16.0 - 20.0	6.1 - 6.2	12.0	2.5	4.00	27	4800	4300	10SS16026
30.0	19.0 - 24.0	6.1 - 6.2	12.0	2.5	4.00	27	4800	4300	10SS16030	
6.4	8.0	1.0 - 2.0	6.5 - 6.6	13.0	2.7	4.00	27	5700	4900	10SS16408
	10.0	3.0 - 4.0	6.5 - 6.6	13.0	2.7	4.00	27	5700	4900	10SS16410
	12.0	4.0 - 6.0	6.5 - 6.6	13.0	2.7	4.00	27	5700	4900	10SS16412
	15.0	5.0 - 8.0	6.5 - 6.6	13.0	2.7	4.00	27	5700	4900	10SS16415
	18.0	8.0 - 11.0	6.5 - 6.6	13.0	2.7	4.00	27	5700	4900	10SS16418
	22.0	11.0 - 15.0	6.5 - 6.6	13.0	2.7	4.00	27	5700	4900	10SS16422
	26.0	15.0 - 19.0	6.5 - 6.6	13.0	2.7	4.00	27	5700	4900	10SS16426
	30.0	19.0 - 24.0	6.5 - 6.6	13.0	2.7	4.00	27	5700	4900	10SS16430