





Niethülse **Stahl verzinkt**
 Nietdorn **Stahl verzinkt**
 Flachrundkopf



DIN EN ISO 15976

$\varnothing d$	l	min - max	\varnothing	$\varnothing d_k$	k max.	$\varnothing d_m$ max.	p min.	[N]	[N]	Code
mm	mm	mm	mm	mm	mm	mm	mm	[N]	[N]	
3.2	6.0	0.5 - 1.5	3.3	6.0	1.3	2.00	25	1300	1150	20SS13206
	8.0	1.5 - 3.0	3.3	6.0	1.3	2.00	25	1300	1150	20SS13208
	9.5	3.0 - 5.0	3.3	6.0	1.3	2.00	25	1300	1150	20SS13209
	12.0	5.0 - 6.5	3.3	6.0	1.3	2.00	25	1300	1150	20SS13212
4.0	6.0	0.5 - 1.5	4.1	8.0	1.7	2.35	25	1700	1550	20SS14006
	8.0	1.5 - 3.0	4.1	8.0	1.7	2.35	25	1700	1550	20SS14008
	9.5	2.5 - 4.5	4.1	8.0	1.7	2.35	25	1700	1550	20SS14009
	10.0	3.0 - 5.0	4.1	8.0	1.7	2.35	25	1700	1550	20SS14010
	12.0	5.0 - 6.5	4.1	8.0	1.7	2.35	25	1700	1550	20SS14012
	15.0	6.5 - 10.5	4.1	8.0	1.7	2.35	25	1700	1550	20SS14015
4.8	8.0	1.0 - 3.0	4.9	9.5	2.0	2.95	27	2800	2400	20SS14808
	9.5	3.0 - 4.5	4.9	9.5	2.0	2.95	27	2800	2400	20SS14809
	12.0	4.0 - 6.5	4.9	9.5	2.0	2.95	27	2800	2400	20SS14812
	16.0	6.5 - 10.5	4.9	9.5	2.0	2.95	27	2800	2400	20SS14816