



Q-Grooved



Niethülse **Aluminium**
 Nietdorn **Stahl verzinkt**
 Flachrundkopf



$\varnothing d$	l	min - max	\varnothing	$\varnothing d_k$	k max.	$\varnothing d_m$ max.	p min.			Code
	mm	mm	mm	mm	mm	mm	mm	[N]	[N]	
3.2	10.0	max. 6.0	3.3 - 3.4	6.0	1.3	2.00	27	1000	750	40AS13210
	14.0	max. 10.0	3.3 - 3.4	6.0	1.3	2.00	27	1000	750	40AS13214
4.0	8.0	max. 4.0	4.1 - 4.2	8.0	1.7	2.45	27	1700	1100	40AS14008
	10.0	max. 6.0	4.1 - 4.2	8.0	1.7	2.45	27	1700	1100	40AS14010
	12.0	max. 8.0	4.1 - 4.2	8.0	1.7	2.45	27	1700	1100	40AS14012
	16.0	max. 12	4.1 - 4.2	8.0	1.7	2.45	27	1700	1100	40AS14016
4.8	8.0	max. 4.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	40AS14808
	10.0	max. 6.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	40AS14810
	11.0	max. 7.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	40AS14811
	12.0	max. 8.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	40AS14812
	14.0	max. 10.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	40AS14814
	16.0	max. 12.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	40AS14816
	18.0	max. 14.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	40AS14818
	20.0	max. 16.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	40AS14820
25.0	max. 21.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	40AS14825	
30.0	max. 26.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	40AS14830	