





Body **Aluminium - RAL9005**  
 Stem **Steel Zinc plated**  
 Dome head



DIN EN ISO 15977

$\varnothing d$	$l$	min - max	$\varnothing$	$\varnothing d_k$	$k$ max.	$\varnothing d_m$ max.	$p$ min.	[N]	[N]	code
mm	mm	mm	mm	mm	mm	mm	mm	[N]	[N]	
<b>3.2</b>	<b>6.0</b>	1.5 - 3.5	3.3 - 3.4	6.0	1.3	2.00	25	700	500	<b>10AS13206</b>
	<b>8.0</b>	3.5 - 5.0	3.3 - 3.4	6.0	1.3	2.00	25	700	500	<b>10AS13208</b>
	<b>10.0</b>	5.0 - 7.0	3.3 - 3.4	6.0	1.3	2.00	25	700	500	<b>10AS13210</b>
	<b>12.0</b>	7.0 - 9.0	3.3 - 3.4	6.0	1.3	2.00	25	700	500	<b>10AS13212</b>
<b>4.0</b>	<b>6.0</b>	1.0 - 3.0	4.1 - 4.2	8.0	1.7	2.45	27	1700	1100	<b>10AS14006</b>
	<b>8.0</b>	3.0 - 5.0	4.1 - 4.2	8.0	1.7	2.45	27	1700	1100	<b>10AS14008</b>
	<b>10.0</b>	5.0 - 6.5	4.1 - 4.2	8.0	1.7	2.45	27	1700	1100	<b>10AS14010</b>
	<b>12.0</b>	6.5 - 8.5	4.1 - 4.2	8.0	1.7	2.45	27	1700	1100	<b>10AS14012</b>
	<b>14.0</b>	8.5 - 10.5	4.1 - 4.2	8.0	1.7	2.45	27	1700	1100	<b>10AS14014</b>
	<b>16.0</b>	10.5 - 12.5	4.1 - 4.2	8.0	1.7	2.45	27	1700	1100	<b>10AS14016</b>
	<b>18.0</b>	12.5 - 14.5	4.1 - 4.2	8.0	1.7	2.45	27	1700	1100	<b>10AS14018</b>
	<b>20.0</b>	14.5 - 16.5	4.1 - 4.2	8.0	1.7	2.45	27	1700	1100	<b>10AS14020</b>
<b>4.8</b>	<b>6.0</b>	1.5 - 2.5	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	<b>10AS14806</b>
	<b>8.0</b>	2.5 - 4.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	<b>10AS14808</b>
	<b>10.0</b>	4.0 - 6.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	<b>10AS14810</b>
	<b>12.0</b>	6.0 - 8.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	<b>10AS14812</b>
	<b>14.0</b>	7.0 - 9.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	<b>10AS14814</b>
	<b>16.0</b>	8.0 - 12.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	<b>10AS14816</b>
	<b>18.0</b>	11.0 - 13.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	<b>10AS14818</b>
	<b>20.0</b>	12.0 - 15.0	4.9 - 5.0	9.5	2.0	2.95	27	2500	1700	<b>10AS14820</b>

For correct order processing; add information to the article code, as referenced below

Example: **10AS148121R9005**

- PARTNUMBER
- PACKAGE/BOX
- RAL COLOUR NUMBER