



Q-STANDARD







Body: **Copper Alloy**
 Stem: **Steel C45**
 Dome head

Hülse: **Kupfer Legierung**
 Dorn: **Stahl C45**
 Flachrundkopf

Cuerpo: **Cobre Aleación**
 Vástago: **Acero C45**
 Remache alomada



DIN EN ISO 16582

D1	L	 min - max	 Ø	D2	k max.	dm ref.	p min.	 [N]	 [N]	code
	mm	mm	mm	mm	mm	mm	mm	[N]	[N]	
3.0	5.0	0.5 - 2.0	3.1	6.3	1.0	1.70	26	950	760	10CS13005
	6.0	2.0 - 3.0								10CS13006
	8.0	3.0 - 5.0								10CS13008
	10.0	5.0 - 7.0								10CS13010
	12.0	7.0 - 9.0								10CS13012
3.2	6.0	0.5 - 2.0	3.3	6.3	1.0	1.75	26	1000	800	10CS13206
	8.0	2.0 - 5.0								10CS13208
	10.0	5.0 - 7.0								10CS13210
	12.0	7.0 - 9.0								10CS13212
4.0	6.0	1.0 - 3.0	4.1	8.0	1.3	2.15	27	1800	1500	10CS14006
	8.0	3.0 - 5.0								10CS14008
	10.0	5.0 - 7.0								10CS14010
	12.0	7.0 - 9.0								10CS14012
	14.0	9.0 - 10.0								10CS14014
	16.0	10.0 - 12.5								10CS14016
4.8	8.0	2.5 - 4.0	4.9	9.5	1.4	2.63	28	2500	2000	10CS14808
	10.0	4.0 - 6.0								10CS14810
	12.0	6.0 - 8.0								10CS14812
	14.0	8.0 - 10.0								10CS14814
	16.0	10.0 - 12.0								10CS14816
	18.0	12.0 - 14.0								10CS14818
	20.0	14.0 - 16.0								10CS14820