





Body **Aluminium**
 Stem **Steel Phosphated**
 Dome head



DIN EN ISO 15973

$\varnothing d$	l	min - max	\varnothing	$\varnothing d_k$	k max.	$\varnothing d_m$ max.	p min.	[N]	[N]	code
mm	mm	mm	mm	mm	mm	mm	mm	[N]	[N]	
3.2	6.5	0.5 - 2.0	3.3	6.0	1.3	1.85	25	1240	1070	20AS13206
	8.0	2.0 - 3.5	3.3	6.0	1.3	1.85	25	1240	1070	20AS13208
	9.5	3.5 - 5.0	3.3	6.0	1.3	1.85	25	1240	1070	20AS13209
	10.5	5.0 - 6.5	3.3	6.0	1.3	1.85	25	1240	1070	20AS13210
	12.5	6.5 - 8.0	3.3	6.0	1.3	1.85	25	1240	1070	20AS13212
4.0	8.0	1.0 - 3.5	4.1	8.0	1.7	2.35	25	2130	1560	20AS14008
	9.5	3.5 - 4.5	4.1	8.0	1.7	2.35	25	2130	1560	20AS14009
	11.0	4.5 - 6.5	4.1	8.0	1.7	2.35	25	2130	1560	20AS14011
	12.5	6.5 - 8.0	4.1	8.0	1.7	2.35	25	2130	1560	20AS14012
	15.0	8.0 - 10.0	4.1	8.0	1.7	2.35	25	2130	1560	20AS14015
4.8	8.0	1.0 - 3.0	4.9	9.5	2.0	2.77	27	3100	2200	20AS14808
	9.5	3.0 - 5.0	4.9	9.5	2.0	2.77	27	3100	2200	20AS14809
	11.0	5.0 - 6.5	4.9	9.5	2.0	2.77	27	3100	2200	20AS14811
	12.5	6.5 - 7.5	4.9	9.5	2.0	2.77	27	3100	2200	20AS14812
	14.0	7.5 - 9.0	4.9	9.5	2.0	2.77	27	3100	2200	20AS14814
	16.0	9.0 - 11.0	4.9	9.5	2.0	2.77	27	3100	2200	20AS14816
	18.0	11.0 - 13.0	4.9	9.5	2.0	2.77	27	3100	2200	20AS14818
	21.0	13.0 - 16.0	4.9	9.5	2.0	2.77	27	3100	2200	20AS14821
6.4	12.5	4.0 - 6.0	6.5	12.5	2.7	3.71	27	4900	3600	20AS16412
	16.0	6.0 - 8.0	6.5	12.5	2.7	3.71	27	4900	3600	20AS16416

Large head										
4.8	13.0	6.0 - 8.0	4.9	14.0	2.5	2.77	27	3100	2200	20AS24813
	18.0	11.0 - 13.0	4.9	14.0	2.5	2.77	27	3100	2200	20AS24818