



# Q-Sealed



Body **Stainless Steel A2**  
 Stem **Stainless Steel C1**  
 Dome head



DIN EN ISO 16585

$\varnothing d$	$l$	min - max	$\varnothing$	$\varnothing d_k$	$k$ max.	$\varnothing d_m$ max.	$p$ min.	[N]	[N]	code
<b>3.2</b>	<b>6.0</b>	0.5 - 1.5	3.3	6.0	1.3	2.15	25	2200	2000	<b>20XY13206</b>
	<b>8.0</b>	1.5 - 3.0	3.3	6.0	1.3	2.15	25	2200	2000	<b>20XY13208</b>
	<b>9.5</b>	3.0 - 5.0	3.3	6.0	1.3	2.15	25	2200	2000	<b>20XY13209</b>
	<b>12.0</b>	5.0 - 7.0	3.3	6.0	1.3	2.15	25	2200	2000	<b>20XY13212</b>
	<b>14.0</b>	7.0 - 9.0	3.3	6.0	1.3	2.15	25	2200	2000	<b>20XY13214</b>
<b>4.0</b>	<b>6.0</b>	0.5 - 1.5	4.1	8.0	1.7	2.75	25	3500	3000	<b>20XY14006</b>
	<b>8.0</b>	1.5 - 3.0	4.1	8.0	1.7	2.75	25	3500	3000	<b>20XY14008</b>
	<b>9.5</b>	2.5 - 4.5	4.1	8.0	1.7	2.75	25	3500	3000	<b>20XY14009</b>
	<b>10.0</b>	3.0 - 5.0	4.1	8.0	1.7	2.75	25	3500	3000	<b>20XY14010</b>
	<b>12.0</b>	5.0 - 6.5	4.1	8.0	1.7	2.75	25	3500	3000	<b>20XY14012</b>
	<b>15.0</b>	6.5 - 10.5	4.1	8.0	1.7	2.75	25	3500	3000	<b>20XY14015</b>
	<b>16.0</b>	7.0 - 11.0	4.1	8.0	1.7	2.75	25	3500	3000	<b>20XY14016</b>
<b>4.8</b>	<b>8.0</b>	1.5 - 3.0	4.9	9.5	2.0	3.20	27	4400	4000	<b>20XY14808</b>
	<b>9.5</b>	3.0 - 4.5	4.9	9.5	2.0	3.20	27	4400	4000	<b>20XY14809</b>
	<b>12.0</b>	4.5 - 6.0	4.9	9.5	2.0	3.20	27	4400	4000	<b>20XY14812</b>
	<b>16.0</b>	6.0 - 10.5	4.9	9.5	2.0	3.20	27	4400	4000	<b>20XY14816</b>
	<b>20.0</b>	10.5 - 14.0	4.9	9.5	2.0	3.20	27	4400	4000	<b>20XY14820</b>

Stainless Steel A4 / Stainless Steel A4 **available on request**